



## SAFETY DATA SHEET

### High Performance Multi Metal Paint

This Safety Data Sheet is prepared in accordance with Annex II to Regulation (EC) No 1907/2006

#### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

##### 1.1. Product identifier

**Product name** High Performance Multi Metal Paint  
**Product No.** HPMM

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** An air-drying, liquid, solvent-borne, paint for industrial and professional use. Apply by manual spray, brush or roller.

##### 1.3. Details of the supplier of the safety data sheet

**Supplier** Magic Bullet Products Ltd  
 Unit B, Marlborough Court  
 Bennerley Road  
 Blenheim Industrial Estate  
 Nottingham  
 NG6 8UY  
 0115 9755555  
 0115 9757005  
 perry@magicbulletproducts.com  
 Perry Wilshire (Director)

**Contact Person**

##### 1.4. Emergency telephone number

Members of the public should contact:  
 In England and Wales: NHS Direct 0845 4647  
 In Scotland: NHS24 08454 24 24 24  
 In Republic of Ireland: 01 809 2166  
 Magic Bullet Products Ltd. 0115 9755555 may also be contacted (Office hours only)

#### SECTION 2: HAZARDS IDENTIFICATION

##### 2.1. Classification of the substance or mixture

**Classification (1999/45/EEC)** Xn;R20/21. R10, R52/53.

##### 2.2. Label elements

**Contains** XYLENE

##### **Labelling**



Harmful

##### **Risk Phrases**

R10	Flammable.
R20/21	Harmful by inhalation and in contact with skin.
R52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

##### **Safety Phrases**

S23	Do not breathe vapour/spray.
S24	Avoid contact with skin.
S36/37	Wear suitable protective clothing and gloves.
S38	In case of insufficient ventilation, wear suitable respiratory equipment.
S43	In case of fire, use alcohol-resistant foam, carbon dioxide or dry powder. Never use water.
S61	Avoid release to the environment. Refer to special instructions/safety data sheets.

# High Performance Multi Metal Paint

## 2.3. Other hazards

This product does not contain any PBT or vPvB substances.

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

### 3.2. Mixtures

<b>XYLENE</b>	<b>12.5 - 20%</b>
<b>CAS-No.: 1330-20-7</b>	<b>EC No.: 215-535-7</b>
<b>Registration Number: 01-2119488216-32-xxx</b>	
Classification (EC 1272/2008) Flam. Liq. 3 - H226 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315	Classification (67/548/EEC) R10 Xn;R20/21 Xi;R38
<b>2-METHOXY-1-METHYLETHYL ACETATE</b>	<b>5 - 10%</b>
<b>CAS-No.: 108-65-6</b>	<b>EC No.: 203-603-9</b>
<b>Registration Number: 01-2119475791-29</b>	
Classification (EC 1272/2008) Flam. Liq. 3 - H226	Classification (67/548/EEC) R10
<b>MODIFIED ZINC ALUMINIUM PHOSPHATE</b>	<b>5 - 10%</b>
Classification (EC 1272/2008) Aquatic Chronic 2 - H411	Classification (67/548/EEC) N;R51/53.
<b>SOLVENT NAPHTHA (PETROLEUM) LIGHT AROMATIC</b>	<b>2.5 - 10%</b>
<b>CAS-No.: 64742-95-6</b>	<b>EC No.: 265-199-0</b>
<b>Registration Number: 01-2119455851-35</b>	
Classification (EC 1272/2008) Flam. Liq. 3 - H226 EUH066 STOT Single 3 - H335, H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411	Classification (67/548/EEC) Xn;R65. Xi;R37. N;R51/53. R10,R66,R67.
<b>ETHYLBENZENE</b>	<b>1 - 5%</b>
<b>CAS-No.: 100-41-4</b>	<b>EC No.: 202-849-4</b>
<b>Registration Number: 01-2119489370-35</b>	
Classification (EC 1272/2008) Flam. Liq. 2 - H225 Acute Tox. 4 - H332	Classification (67/548/EEC) F;R11 Xn;R20
<b>BUTYL ACETATE -norm</b>	<b>1 - 5%</b>
<b>CAS-No.: 123-86-4</b>	<b>EC No.: 204-658-1</b>
<b>Registration Number: 01-2119485493-29-xxxx</b>	
Classification (EC 1272/2008) Flam. Liq. 3 - H226 EUH066 STOT Single 3 - H336	Classification (67/548/EEC) R10 R66 R67

## High Performance Multi Metal Paint

<b>1,2,4-TRIMETHYLBENZENE</b>		<b>1 - 5%</b>
<b>CAS-No.: 95-63-6</b>		<b>EC No.: 202-436-9</b>
Classification (EC 1272/2008) Flam. Liq. 3 - H226 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 STOT Single 3 - H335 Aquatic Chronic 2 - H411	Classification (67/548/EEC) R10 Xn;R20 Xi;R36/37/38 N;R51/53	
<b>MESITYLENE</b>		<b>1 - 5%</b>
<b>CAS-No.: 108-67-8</b>		<b>EC No.: 203-604-4</b>
Classification (EC 1272/2008) Flam. Liq. 3 - H226 STOT Single 3 - H335 Aquatic Chronic 2 - H411	Classification (67/548/EEC) R10 Xi;R37 N;R51/53	
<b>99422018</b>		<b>0.1 - 1%</b>
<b>CAS-No.:</b>		<b>EC No.: 907-495-0</b>
		<b>Registration Number: 01-2119545465-35-0000</b>
Classification (EC 1272/2008) Aquatic Chronic 3 - H412	Classification (67/548/EEC) R52.	
<b>CUMENE</b>		<b>0.1 - 1%</b>
<b>CAS-No.: 98-82-8</b>		<b>EC No.: 202-704-5</b>
Classification (EC 1272/2008) Flam. Liq. 3 - H226 STOT Single 3 - H335 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411	Classification (67/548/EEC) R10 Xn;R65 Xi;R37 N;R51/53	
<b>QUATERNARY AMMONIUM COMPOUNDS, COCOALKYLETHYLDIMETHYL, ET SULFATES</b>		<b>0.1 - 1%</b>
<b>CAS-No.: 68308-64-5</b>		<b>EC No.: 269-662-8</b>
Classification (EC 1272/2008) Acute Tox. 4 - H302 Skin Corr. 1B - H314 Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410	Classification (67/548/EEC) Xn;R22. C;R34. N;R50/53.	
<b>ZINC OXIDE</b>		<b>0.1 - 1%</b>
<b>CAS-No.: 1314-13-2</b>		<b>EC No.: 215-222-5</b>
Classification (EC 1272/2008) Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410	Classification (67/548/EEC) N;R50/53	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

# High Performance Multi Metal Paint

## Ingredient notes

Substances presenting a health or environmental hazard within the meaning of the Dangerous Substances Directive 67/548/EEC or Regulation (EC) No. 1272/2008, assigned a Community workplace exposure limit, classified as PBT/vPvB or included in the Candidate List.

## Composition Comments

The data shown are in accordance with the latest EC Directives.

## SECTION 4: FIRST AID MEASURES

### 4.1. Description of first aid measures

#### General information

In all cases of doubt, or when symptoms persist, seek medical attention.

Never give anything by mouth to an unconscious person.

If unconscious place in recovery position and seek medical advice.

#### Inhalation

Remove to fresh air, keep patient warm and at rest.

If breathing is irregular or stopped, administer artificial respiration.

#### Ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention.

Keep at rest. Do NOT induce vomiting.

#### Skin contact

Remove contaminated clothing.

Wash skin thoroughly with soap and water or use recognised skin cleanser.

Do NOT use solvents or thinners.

#### Eye contact

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

### 4.2. Most important symptoms and effects, both acute and delayed

#### Inhalation.

In case of overexposure, organic solvents may depress the central nervous system causing dizziness and intoxication, and at very high concentrations unconsciousness and death.

#### Ingestion

Ingestion may cause nausea, diarrhoea and vomiting.

#### Skin contact

Prolonged or repeated contact with skin may cause soreness, irritation or dry skin due to a defatting action.

#### Eye contact

The liquid splashed in the eyes may cause irritation and reversible damage.

### 4.3. Indication of any immediate medical attention and special treatment needed

See above.

## SECTION 5: FIREFIGHTING MEASURES

### 5.1. Extinguishing media

#### Extinguishing media

recommended: alcohol resistant foam, CO<sub>2</sub>, powders, water spray/mist

#### Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

### 5.2. Special hazards arising from the substance or mixture

#### Unusual Fire & Explosion Hazards

Fire will produce dense black smoke.

Exposure to decomposition products may cause a health hazard.

Appropriate breathing apparatus may be required.

### 5.3. Advice for firefighters

#### Special Fire Fighting Procedures

Cool closed containers exposed to fire with water.

Do not allow run-off from fire fighting to enter drains or water courses.

#### Protective equipment for fire-fighters

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1. Personal precautions, protective equipment and emergency procedures

# High Performance Multi Metal Paint

Exclude non-essential personnel. Exclude sources of ignition and ventilate the area.

Avoid breathing vapours.

Refer to protective measures listed in sections 7 and 8.

## **6.2. Environmental precautions**

Do not allow to enter drains or watercourses.

If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations. Vapours are heavier than air. They will spread along the ground and collect in low or confined areas (sewers, basements, tanks).

## **6.3. Methods and material for containment and cleaning up**

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13).

Clean preferably with a detergent - avoid use of solvents.

## **6.4. Reference to other sections**

See Section 12 for additional ecological information.

## **SECTION 7: HANDLING AND STORAGE**

### **7.1. Precautions for safe handling**

The Manual Handling Operations Regulations may apply to the handling of containers of this product.

To assist employers, the following method of calculating the weight for any pack size is given. Take the pack size volume in litres and multiply this figure by the specific gravity value given in Section 9. This will give the net weight of the coating in kilograms. Allowance will then have to be made for the immediate packaging to give an approximate gross weight.

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits.

In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded.

Electrical equipment should be protected to the appropriate standard.

Mixture may charge electrostatically: always use earthing leads when transferring from one container to another.

Operators should wear anti-static footwear and clothing and floors should be of the conducting type.

Isolate from sources of heat, sparks and open flame.

Non-sparking tools should be used.

Avoid skin and eye contact.

Avoid the inhalation of dust, particulates and spray mist arising from the application of this mixture.

Avoid inhalation of dust from sanding.

Smoking, eating and drinking should be prohibited in application area.

For personal protection see Section 8.

Never use pressure to empty: container is not a pressure vessel.

Always keep in containers of same material as the original one.

Comply with the health and safety at work laws.

Do not allow to enter drains or water courses.

Wash hands before eating and before leaving the site.

Remove contaminated clothing and protective equipment before entering eating areas.

Information on fire and explosion protection.

Vapours are heavier than air and may spread along floors.

Vapours may form explosive mixtures with air.

When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.

### **7.2. Conditions for safe storage, including any incompatibilities**

Store in accordance with the Dangerous Substances and Explosive Atmospheres Regulations (DSEAR). The requirements are given in the HSE Approved Code of Practice and Guidance, Storage of Dangerous Substances: DSEAR.

The principles contained in the HSE guidance note Chemical Warehousing: The Storage of Packaged Dangerous Substances, should be observed when storing this product.

Notes on joint storage.

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

Additional information on storage conditions

Observe label precautions.

Store between 5 and 25 °C in a dry, well ventilated place away from sources of heat and direct sunlight.

Keep container tightly closed.

Keep away from sources of ignition.

No smoking.

Prevent unauthorised access.

Containers which are opened must be carefully resealed and kept upright to prevent leakage.

### **7.3. Specific end use(s)**

The identified uses for this product are detailed in Section 1.2.

## **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

### **8.1. Control parameters**

## High Performance Multi Metal Paint

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
1,2,4-TRIMETHYLBENZENE	WEL	25 ppm	125 mg/m3			
2-METHOXY-1-METHYLETHYL ACETATE	WEL	50 ppm(Sk)	274 mg/m3(Sk)	100 ppm(Sk)	548 mg/m3(Sk)	
99422018	WEL		10 mg/m3 resp.dust			
BUTYL ACETATE -norm	WEL	150 ppm	724 mg/m3	200 ppm	966 mg/m3	
CUMENE	WEL	25 ppm	125 mg/m3	50 ppm	250 mg/m3	Sk
ETHYLBENZENE	WEL	100 ppm	441 mg/m3	125 ppm	552 mg/m3	Sk
SOLVENT NAPHTHA (PETROLEUM) LIGHT AROMATIC	SUP	25 ppm	120 mg/m3			
XYLENE	WEL	50 ppm	220 mg/m3	100 ppm	441 mg/m3	Sk

WEL = Workplace Exposure Limit.

Sk = Can be absorbed through skin.

### Ingredient Comments

According to EH40 - List of approved workplace exposure limits.

For dust the 8 hour TWA's are:-

Respirable dust 4 mg/cu.m (WEL)

Total inhalable dust 10 mg/cu.m (WEL)

### Biological Limit Values

Xylene:- 650 mmol methyl hippuric acid/mol creatinine in urine

Post shift sampling time

## 8.2. Exposure controls

### Protective equipment



### Process conditions

Provide eyewash station.

### Engineering measures

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction.

If local exhaust ventilation and good general extraction are not sufficient to maintain concentrations of solvent vapour below the OEL, suitable respiratory protection must be worn.

Dry sanding, flame cutting and/or welding of the dry paint film may give rise to dust and/or hazardous fumes. Wet sanding should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.

See Respiratory Equipment below.

### Respiratory equipment

Air-fed protective respiratory equipment should be worn by spray operators even when good ventilation is provided.

In other operations, if local exhaust ventilation and good general extraction are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

### Hand protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

For prolonged or repeated handling, use chemically resistant gloves made of Viton.

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance and effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin, they should however not be applied once exposure has occurred.

### Eye protection

Use safety eyewear designed to protect against splash of liquids.

### Other Protection

Wear appropriate clothing to prevent any possibility of skin contact.

### Hygiene measures

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

# High Performance Multi Metal Paint

## Skin protection

Personnel should wear anti-static clothing made of natural fibre or of high temperature resistant synthetic fibre.

## Environmental Exposure Controls

Refer to the Environmental Protection Act and the Control of Pollution Act. Do not allow to enter drains or water courses.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

Appearance	Viscous liquid.
Colour	Various
Odour	Aromatic hydrocarbons.
Solubility	Immiscible with water
Initial boiling point and boiling range	137 - 180°C 760 mm Hg
Melting point (°C)	-24°C
Relative density	1.35 - 1.45 @ 20°C
Vapour density (air=1)	Heavier than air
Vapour pressure	0.67 kPa 21°C
pH-Value, Conc. Solution	Not determined.
Viscosity	4.0 - 5.0 poise Rotoinner @ 20°C
Flash point (°C)	23 - 32°C Sh CC (Setaflash closed cup).
Auto Ignition Temperature (°C)	465 - 525°C
Flammability Limit - Lower(%)	0.6
Flammability Limit - Upper(%)	10.8

### 9.2. Other information

Volatile Organic Compound (VOC)	490 - 500 g/litre
Volatile Organic Compound (VOC)	35 - 37 g/100 g

## SECTION 10: STABILITY AND REACTIVITY

### 10.1. Reactivity

Stable under recommended storage and handling conditions (see section 7).  
When exposed to high temperatures may produce hazardous decomposition products.

### 10.2. Chemical stability

Stable under recommended storage and handling conditions (see section 7).  
In a fire, hazardous decomposition products may be produced.

### 10.3. Possibility of hazardous reactions

Fire will produce dense black smoke.  
Exposure to decomposition products may cause a health hazard.  
Appropriate breathing apparatus may be required.

### 10.4. Conditions to avoid

Avoid heat, flames and other sources of ignition.

### 10.5. Incompatible materials

#### Materials To Avoid

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions

### 10.6. Hazardous decomposition products

such as carbon monoxide and dioxide, smoke, oxides of nitrogen etc.

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1. Information on toxicological effects

#### General information

There are no data available on the mixture itself.

The mixture has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and classified for toxicological hazards accordingly. See sections 2 and 3 for details.

# High Performance Multi Metal Paint

## Inhalation

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system.

## Ingestion

Ingestion may cause nausea, diarrhoea and vomiting.

## Skin contact

Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

## Eye contact

Irritating and may cause redness and pain. The liquid splashed in the eyes may cause irritation and reversible damage.

## Route of entry

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

## Medical Symptoms

Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin.

<b>Name</b>	<b>XYLENE</b>
<b>Toxic Dose 1 - LD 50</b>	>4300 mg/kg (oral rat)
<b>Toxic Dose 2 - LD 50</b>	>4400 mg/kg (ipr-rat)
<b>Toxic Conc. - LC 50</b>	>27.6 mg/l/4h (inh-rat)

## SECTION 12: ECOLOGICAL INFORMATION

### Ecotoxicity

The mixture has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and is classified for eco-toxicological properties accordingly. See Sections 2 and 3 for details.

#### 12.1. Toxicity

#### Acute Fish Toxicity

There is no toxicity data for this product.

#### 12.2. Persistence and degradability

#### Degradability

There are no data on the degradability of this product.

#### 12.3. Bioaccumulative potential

#### Bioaccumulative potential

No data available on bioaccumulation.

#### 12.4. Mobility in soil

#### Mobility:

There is no data on the mobility of the product.

#### 12.5. Results of PBT and vPvB assessment

This product does not contain any PBT or vPvB substances.

#### 12.6. Other adverse effects

Not determined.

## SECTION 13: DISPOSAL CONSIDERATIONS

### General information

Do not allow to enter drains or water courses.

#### 13.1. Waste treatment methods

Waste and emptied containers are controlled wastes and should be disposed of in accordance with "The Environment Protection (Duty of Care) Regulations" (in England, Scotland, Wales) or The Controlled Waste (Duty of Care) Regulations (in Northern Ireland).

#### Waste Class

The European Waste Catalogue classification of this product, when disposed of as waste is:

Waste Code: Name of Waste (according to Directive 2000/532/EC):

08 01 11 Waste paint and varnish containing organic solvents or other dangerous substances

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

For further information contact your local waste authority.

Using information provided in this safety data sheet, advice should be obtained from the local waste authority on the classification of empty containers.



# High Performance Multi Metal Paint

Empty containers must be scrapped or reconditioned.

Dispose of empty containers contaminated by the product in accordance with local or national legal provisions.

## SECTION 14: TRANSPORT INFORMATION

### Road Transport Notes

VISCOUS FLAMMABLE LIQUID DEROGATION

In pack sizes less than 450 litres, under the terms of 2.2.3.1.5, this product is not subject to the provisions of ADR. These provisions do not apply to air transport.

### Sea Transport Notes

VISCOUS FLAMMABLE LIQUID DEROGATION:

In pack sizes up to and including 30 litres, under the terms of 2.3.2.5, this product is not subject to the packaging, labelling and marking requirements of the IMDG Code, but both full documentation and placarding of cargo transport units is still required.

### Air Transport Notes

VISCOUS FLAMMABLE LIQUID DEROGATION:

The "viscosity exemption" provision does not apply to air transport. The information provided in this section may not be valid for transport by Air. Please call the number in section 1 of this safety data sheet to obtain more information about the transport of this product by air.

#### 14.1. UN number

UN 1263

#### 14.2. UN proper shipping name

PAINT

#### 14.3. Transport hazard class(es)

3

ADR Label No.

3

Transport Labels



#### 14.4. Packing group

PG III

#### 14.5. Environmental hazards

Environmentally Hazardous Substance/Marine Pollutant

No.

#### 14.6. Special precautions for user

Transport within the user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of accident or spillage.

EMS

F-E, S-E

Tunnel Restriction Code

(D/E)

#### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not relevant

## SECTION 15: REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **UK Regulatory References**

The provisions of the Health and Safety at Work etc. Act and the Control of Substances Hazardous to Health Regulations apply to the use of this product at work.

The information contained in this safety data sheet does not constitute the users own assessment of workplace risks as required by other health and safety legislation.

#### **Environmental Listing**

The Environmental Protection (Duty of Care) Regulations 1992 (SI 1992:2839), TSO.

Hazardous Waste Regulations 2005 (SI 2005:894) and amendments

#### **Statutory Instruments**

The Control of Substances Hazardous to Health Regulations 2002(SI 2002:1689) and amendments.

The Dangerous Substances & Explosive Atmospheres Regulations 2002(SI 2002:2776).

The Manual Handling Operations Regulations 1992, (SI 1992:2793)and amendment, The Stationery Office.

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (S.I 2009 No. 716).

# High Performance Multi Metal Paint

## Approved Code Of Practice

Control of Substances Hazardous to Health (Fifth Edition) (HSE Books L5)  
Storage of Dangerous Substances (2003) (HSE Books L135)  
Dangerous Substances and Explosive Atmospheres Regulations 2002, (HSE Books L138)

## Guidance Notes

The Approved Classification and Labelling Guide, 6th edition.  
COSHH Essentials: easy steps to control chemicals, HSG 193. HSE books. Control Guidance Sheets, which may be relevant to the particular conditions of use, can also be found in this publication.  
Chemical Warehousing: Storage of Flammable Liquids in Containers(HSG51), HSE Books.  
Storage: Packaged Dangerous Substances HSG71, HSE.  
A Guide to Working with Solvents (INDG 272), HSE.  
Spraying of Flammable Liquids HSG178  
Workplace Exposure Limits EH40.  
Best Practice Guideline 5 "Safe Use of Gloves (June 2010) published by the European Solvents Industry Group (ESIG) available at [www.esig.org/en/library/publications/best-practice-guides](http://www.esig.org/en/library/publications/best-practice-guides)

## EU Legislation

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments.  
Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments.

## National Regulations

Workplace Exposure Limits 2005 (EH40)

### 15.2. Chemical Safety Assessment

No chemical safety assessment has been carried out for this product by the supplier..

### 15.3 Paints Directive 2004/42/EC

VOC Content: EU limit for this product (Cat A/i) is: 500 g/litre  
This product contains maximum 500 g/litre VOC.

## SECTION 16: OTHER INFORMATION

### General information

The product should not be used for purposes other than those shown in Section 1.

### Revision Comments

This is the first issue.

<b>Issued By</b>	Product Steward
<b>Revision Date</b>	20 June 2013
<b>Revision</b>	1.00

### Risk Phrases In Full

R34	Causes burns.
R10	Flammable.
R20/21	Harmful by inhalation and in contact with skin.
R20	Harmful by inhalation.
R22	Harmful if swallowed.
R52	Harmful to aquatic organisms.
R65	Harmful: may cause lung damage if swallowed.
R11	Highly flammable
R36/37/38	Irritating to eyes, respiratory system and skin.
R37	Irritating to respiratory system.
R38	Irritating to skin.
R66	Repeated exposure may cause skin dryness or cracking.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R67	Vapours may cause drowsiness and dizziness.
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

# High Performance Multi Metal Paint

## Hazard Statements In Full

H319	Causes serious eye irritation.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H226	Flammable liquid and vapour.
H332	Harmful if inhaled.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H412	Harmful to aquatic life with long lasting effects.
H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.
H335	May cause respiratory irritation.
EUH066	Repeated exposure may cause skin dryness or cracking.
H411	Toxic to aquatic life with long lasting effects.
H410	Very toxic to aquatic life with long lasting effects.
H400	Very toxic to aquatic life.

## Disclaimer

The information of this SDS is based on the present state of our knowledge and on current legislation.

It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.

The product should not to be used for purposes other than those shown in section 1 without first referring to the supplier and obtaining written handling instructions.

As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements or relevant legislation are complied with.

The information in this safety data sheet does not constitute the user's own assessment of workplace risks as required by other health and safety legislation.