

SAFETY DATA SHEET

SPEED STRIP SOLVENT BASED PAINT REMOVER

Page: 1

Compilation date: 11/04/2013

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: SPEED STRIP SOLVENT BASED PAINT REMOVER

Product code: FLAM/GEL/DIO

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Specialist Paint and Surface Coating Remover

1.3. Details of the supplier of the safety data sheet

Company name: MAGIC BULLET PRODUCTS
UNIT B MARLBOROUGH COURT
BENNERLEY ROAD
NOTTINGHAM
NG6 8UY

Tel: 0115 597 55555

Email: mike.keeps@ntlworld .com

1.4. Emergency telephone number

Emergency tel: 0115 597 55555

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Flam. Liq. 2: H225

Classification under CHIP: F+: R12

Most important adverse effects: Highly flammable liquid and vapour.

2.2. Label elements

Label elements under CLP:

Hazard statements: H225: Highly flammable liquid and vapour.

Signal words: Danger

Hazard pictograms: GHS02: Flame



Precautionary statements: P243: Take precautionary measures against static discharge.

P242: Use only non-sparking tools.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P303+361+353: IF ON SKIN (or hair): Remove immediately all contaminated

[cont...]

SAFETY DATA SHEET

SPEED STRIP SOLVENT BASED PAINT REMOVER

Page: 2

clothing. Rinse skin with water/shower.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

P370+378: In case of fire: Use foam for extinction.

2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This product is not identified as a PBT substance.

Section 3: Composition/information on ingredients

3.1. Substances

Chemical identity: SPEED STRIP SOLVENT BASED PAINT REMOVER

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin.
Drench the affected skin with running water for 10 minutes or longer if substance is still on skin.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Do not induce vomiting. If conscious, give half a litre of water to drink immediately.
Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: There may be a feeling of tightness in the chest with shortness of breath.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Alcohol resistant foam. Water spray. Carbon dioxide. Dry chemical powder.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Highly flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture. Vapour may travel considerable distance to source of ignition and flash back.

[cont...]

SAFETY DATA SHEET

SPEED STRIP SOLVENT BASED PAINT REMOVER

Page: 3

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Notify the police and fire brigade immediately. Eliminate all sources of ignition. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Do not use equipment in clean-up procedure which may produce sparks. Absorb into dry earth or sand. Clean-up should be dealt with only by qualified personnel familiar with the specific substance.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Smoking is forbidden. Use non-sparking tools. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting and electrical equipment are not a source of ignition.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits: No data available.

[cont...]

SAFETY DATA SHEET

SPEED STRIP SOLVENT BASED PAINT REMOVER

Page: 4

8.1. DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

Respiratory protection: Respiratory protection not required.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Colourless

Odour: Characteristic odour

Evaporation rate: Moderate

Solubility in water: Slightly soluble

Also soluble in: Most organic solvents.

Viscosity: Viscous

Boiling point/range°C: >35

Flash point°C: -6

Relative density: 1.004

pH: Approx. 7

VOC g/l: 955

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions. Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

[cont...]

SAFETY DATA SHEET

SPEED STRIP SOLVENT BASED PAINT REMOVER

Page: 5

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

BENZYL ALCOHOL

IVN	RAT	LD50	53	mg/kg
ORL	MUS	LD50	1360	mg/kg
ORL	RAT	LD50	1230	mg/kg

Toxicity values: No data available.

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: There may be a feeling of tightness in the chest with shortness of breath.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

[cont...]

SAFETY DATA SHEET

SPEED STRIP SOLVENT BASED PAINT REMOVER

Page: 6

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1993

14.2. UN proper shipping name

Shipping name: FLAMMABLE LIQUID, N.O.S.

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group: II

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E

Transport category: 2

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and 3: H225: Highly flammable liquid and vapour.

R12: Extremely flammable.

Legal disclaimer: The above information is believed to be correct but does not purport to be all

[cont...]

SAFETY DATA SHEET

SPEED STRIP SOLVENT BASED PAINT REMOVER

Page: 7

inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.